## **CONCRETE MIXER SERIE 625**

Hydrostatic 4x4 by 4 wheels drive

With anti-skating system.

Diesel Engine Power N° cylinders Cooling

Transmission

**Emission Standards** 

H-625H-DG KOHLER 25,5 CV 4 Water cooler

Stage V

H-625T4-DG KOHLER 24,5 CV 3 Water cooler

Stage V


Mechanical traction 4x4 by Cardan.



H-625H-DG

Self-loading and Swivel Unloading Concrete Mixer (180°) at 761 mm





Dimensions (mm)

**PIQUERSA** 

A - 3.500 Maximum length

B - 1.675 Wheelbase

C – 485 Rear extension D – 2.360 Maximum height

F - 1.725 Maximum width

G = 761 Unloading height

H – 300 Unloading length


Front track width: 1.370 Front track width: 1.470

Single Dry Plate. Maximum gradient: 41%

## H-625T4-DG

Self-loading and Swivel Unloading Concrete Mixer (180°) at 741 mm





Dimensions (mm)

A - 3.500 Maximum length

B - 1.675 Wheelbase

C - 500 Rear extension

D - 2.340 Maximum height

F - 1.660 Maximum width

G = 741 Unloading height

H - 344 Unloading length

Front track width: 1.260

Front track width: 1.260

Maximum gradient: 53%

Gearbox		4+4 speeds with reverser
Brakes	Hydrostatics / Parking: Oil bath bearing, electric activation.	Hydraulics 4 Wheels.
Clutch	Not available.	Single dry plate.
Steering	Hydraulic.	
Chassis	Rigid.	
Driver Seat	Anatomical, homologate, adjustable according to the drive weight and with homologated seat belt.	
Wheels	H-625H-DG	H-625T4-DG
Front	11,0 x 65 - 12"	27 x 8,50 - 15"
Rear	11,0 x 65 - 12"	27 x 8,50 - 15"
Outer Turning Radius	395 cm	
Tanks		
Oil	34 I	
Fuel	28	
Hopper		
Drum	625 I	
Mix	Maximum: 410 I	
Maximum trailer load		
(Optional Hook)	H-625H-DG	H-625T4-DG
Without Brakes	1.000 kg	1.000 kg
With Brakes	2.100 kg	2.100 kg
Unladen Weight	2.325 kg	2.015 kg
Equipment	Flashing beacon. Seat belt. Electrical Start and Stop. Left rear-view mirror.	
	Reverse Warning Signal. Hand throttle. Joystick multifunction. * (Only H-625H-DG)	
Security	Roll-cage / Safety roof.	
Options	Windscreen and windscreen wipers. Homologated Lights. Seat belt with micro.	
Options	Windscreen and windscreen wipers. Homologated Lights. Seat belt with micro.	

Passenger seat. Closed cabin. Heating. Hook. Wheels 10.0/75-15.3".

2 speeds \*. (Only H-625H-DG)

Rear Water tank 350 L. High pressure kit. Self-priming water pump for drum filling.